

The Right Stuff

DID YOU KNOW...

Silicone should set for 2 to 6 hours...

The Right Stuff only takes **1 MINUTE!**

Don't have a gasket in stock?

This latest elastomeric rubber gasket technology is blowout resistant and outperforms pre-cut gaskets.

APPLY – ASSEMBLE – DRIVE!



**NEVER THE WRONG GASKET
BECAUSE IT'S ALWAYS THE...**



***Note:** Not to be used with head gasket, fuel or exhaust applications!

Silicone Gasket Makers



**#82194
ULTRA GREY**
Import Vehicles
Aluminum Parts
Synthetic Fluids
OEM Specified
No Contact w/Fuels
#85084 PowerBead Can



**#82180
ULTRA BLACK**
Ford, GM, Chrysler
Cast Iron Parts
OEM Specified
Oil Resistant
No Contact w/Fuels
#85080 PowerBead Can



**#81878
ULTRA COPPER**
High Temperature Applications
Exhaust Manifolds
High Performance Applications
Turbos, Headers
No Contact w/Fuels

Ultra Series Gasket Makers should cure a **minimum 2 hrs.** (recommend 24 hrs.) before returning vehicle to service!



**#80022
Original Sensor-Safe BLUE**
General Automotive Gasketing
No Contact w/Fuels



**#81160
High-Temp RED**
High Temperature/Heavy
Duty
Applications
No Contact w/Fuels

Original Blue & High Temp Red Gasket Makers should cure a **minimum 6 hrs.** (recommend 24 hrs.) before returning vehicle to service!

Specialty Gasket Makers



**#29132
MOTOSEAL**
For 2 & 4 cycle engines
Case Halves & Uneven Joints
Bonds Fully In 20 Minutes
Fuel Resistant



**#51813
ANAEROBIC GASKET MAKER**
Seals 2 Machined Metal Parts
Case Halves, Gear Cases
Machined Housings
Fuel Resistant



**#81180
ATF/RTV **NEW!****
Seals Transmissions
against all ATF's including
Newer Fluids w/Harsh
Additives



**#81182
GEAR OIL RTV **NEW!****
Seals Differentials &
Transfer Cases against
all Gear Oils including
Newer Fluids w/Harsh
Additives

Gasket Sealants

These products are used to aid in sealing pre-cut gaskets (paper, cork, felt, composite, rubber and metal gaskets). Sealants prevents gasket from moving during installation. All are fuel resistant!



**#85249
HYLOMAR**
Most Chemical Resistant Sealant In Our Line
Works With All Pre-Cut Gaskets (no rubber)
Allows Repeated Disassembly/Reassembly
Without Damaging Gasket or Gasket Surface
Non-Hardening



**#85409
RUBBER GASKET SEALANT**
Aids In Sealing
Gasket Won't Crimp
Gasket Won't Slip Out Of Flange
Easy Repositioning If Necessary
Extends Life Of Rubber



**#80697
COPPER SPRAY HI-TEMP SEALANT**
High Temperature Applications
Seals Instantly
Cylinder Head Gaskets (steel shim only)
Exhaust Manifold Gaskets



**#80064
HIGH TACK GASKET SEALANT**
Paper Gaskets
Cork Gaskets
Fast Drying, All Purpose Sealant



**#80016
FORM-A-GASKET #2**
Easy Disassembly
Slow-drying, Non-Hardening
Valve Cover & Oil Pan Gaskets

Threadlockers

- Threadlockers Secure Fasteners In Place!
- Specified By Automotive Manufacturers!
- Fills Open Space Between Threads & Application To Keep Corrosion Out!
- Threadlockers Cure In The Absence Of Air and Presence Of Metal!

WHAT COLOR SHOULD I USE?

ANSWER: WHAT IS THE DIAMETER OF THE FASTENER?

PURPLE	= Fasteners 1/4" or less
BLUE	= Fasteners 1/4" to 3/4" – Removable w/Hand Tool
RED	= Fasteners 3/8" to 1" – Think Before You Use!
GREEN	= Preassembled Fasteners #2 up to 1/2"



SURFACE PREP - #24163

- CUT CURING TIME BY 50%
 - RECOMMENDED USE IN COLD WEATHER
 - A Must When Fastener Metals Are Inactive!
- IF A MAGNET CAN'T STICK TO IT... YOU NEED TO "PREP IT!"**

Works With All Anaerobic Products



6 ml Size



36 ml Size

Threadlockers Are Available In Liquid And Gel Formulas



GEL TWIST



GEL SQUEEZE

NEW!

Blue: #24200
Red: #27100

Blue: #24240
Red: #27140

Blue: #24010
Red: #27010

Blue: #24005
Red: #27005

Thread Sealant

Thread Sealant seal and secure metal threaded pipes and fittings against fluids and pressure.

- Won't Shred or Foul Out A System Like Teflon Tape Can Do!
- Withstands Up To 10,000 PSI.



#59214

HIGH TEMPERATURE THREAD SEALANT

Aluminum Applications
Head Bolts
Oil PSI Sending Units/Sensors
Oil & Coolant Lines
Fuel Fittings, Brake & Power Steering Fittings



#59235



Anti-Seize and Dielectric Grease Lubricants



#80078



#81343

ANTI-SEIZE LUBRICANT

Prevents Seizing, Galling & Corrosion
Makes Future Disassembly Easy
Spark Plugs
Oxygen Sensors
Cylinder Head & Exhaust Manifold Bolts



#22058



#81150

DIELECTRIC/BULB & ELECTRICAL CONNECTOR GREASE

Protects Connections From Corrosion
Provide Easy Future Removal
Prevents Voltage Leakage
Extends Life of Light Bulbs
Excellent On Electrical Connections, Spark Plug Boots, Trailer Hitches, Headlamps

Disc Brake Caliper Lubes

- Outperforms Ordinary Caliper Grease & Traditional DB Quiet
- Allows Caliper Movement to Prevent Premature Brake Pad Wear
- Can Be Applied to Contact Points on Back of Pad
- Prevents Caliper Bolts From Seizing
- Pure Synthetic Lube/Environmentally Safe
- Compatible w/Internal & External Rubber & Plastic Hardware
- Will Not Wash Out
- Apply to Sleeves, Bushings, Caliper Pins, Bolts, Parking Brake Pistons



#24125
BEST CHOICE!
NEW!
Permatex Ceramic Extreme Brake Parts Lubricant
Temp Range: -50°F to 3,000°F



#24110
GOOD CHOICE
Temp Range: -40°F to +400°F

Gasket Remover



#80645
NEW! GASKET REMOVER – LOW VOC FORMULA

NEW!

- Approved For Use in All 50 States
- Removes All Solvent-Based Gasketing (Form-A-Gaskets #1 & #2), High Tack
- Removes Indian Head Shellac, Copper Spray-A-Gasket, Hylomar
- Removes Anaerobic Gasket Maker Baked-On Gaskets and Cements
- Works On The Most Stubborn or Baked-On Gaskets in 15 – 20 Minutes
- Brush-Tip Applicator Provides Easy Application and Pin-Point Control

REPRESENTED BY
CONNOLLY SALES AND MARKETING
1384 PITTSFORD MENDON ROAD
MENDON, NY 14506
PHONE: (585) 624-2723
WWW.CONNOLLYSALES.COM
Jim Connolly & Jerry Spexarth

VISIT WWW.PERMATEX.COM TODAY!

1-877-376-2839 (OPTION #2 FOR TECHNICAL ASSISTANCE!)